

TECHNICAL – LIGHTING EQUIPMENT

Lighting Equipment

- Control Desk – Strand VL64 – 64 Scene Masters
- Tracking Backup – Strand VL16
- Dimmers – 120 Channels Solution 12 Dimmers, 36 Channels Bytesize
Dimmers/patch bay located on the first gallery, OP side. Bytesize dimmers can be located elsewhere.
- 1 x D/Amp next to dimmer racks
- DMX and ethernet patch points around stage and at operator positions
- 2 x Jands DD-8 Opto-Isolators
- HP PDA Wireless Riggers Remote

Luminaries

- 22 x Selecon Pacific Profiles, 12°-28°, 240V 1.2k
- 28 x Selecon Pacific Profiles, 23°-50°, 240V 1.2k
- 4 x Selecon Pacific Profiles, assorted very wide snouts, 240V 1.2k
- 30 x Selecon Acclaim Profiles 18°, 34°, 240V 650w
- 6 x Selecon Aurora, 240V 1k, quad cyc lights
- 24 x Selecon Multi-par, 240V 575w (3 x interchangeable lenses – narrow, medium and wide)
- 4 x Martin Entour 250
- 4 x Martin Wash 250
- 4 x Martin Wash 600
- 1 x Golden Strobe 2.7kw
- 1 x UV Blacklight
- 2 x Selecon Rua Series II Follow Spots

Lighting Accessories

- 6 x Telescopic Floor Stands
- 15 x H – Stands
- 13 x Iris for 1k Pacific Profiles
- 4 x Iris for Acclaim 650w Profiles
- Assorted Gobos
- 1 x 24" Mirror ball
- 6 x Lighting Ladders
(fitted with 4 x multi pars)
Ladders have a capacity of six lamps each (multi pars or 650W profiles)

Lighting Rig

The standard rig is 3 colour wash O/head and Front of House in Lee 103, 106, 107 and 132 (L106 in FOH Bridge 2 only). We have pre cut stock of R132 for FOH.

FOH BRIDGES:

BRIDGE TWO	22 x 1.2kw, Pacific Profiles 15°-28°, (includes 2 Specials)
BRIDGE ONE	18 x 1.2kw, Pacific Profiles 23°-50° (includes 6 Specials)
PERCHES (each side)	6 x 650w, Acclaim Profiles 18°-34°
LX ONE	12 x 1.2kw Fresnel – 3 colour wash down stage 6 x 650w Acclaim Profiles 18°-34°
LX TWO	12 x 1.2kw Fresnel – 3 colour wash centre stage 6 x 650w Acclaim Profiles 18°-34°
LX THREE	12 x 1.2kw Fresnel – 3 colour wash upstage 6 x 650w Acclaim Profiles 18°-34°
LX FOUR	6 x 4 1.25kw Aurora Quad Cyc Floods